



LEGRAND STATE REPORTING MODULEULE CX³ - AUXILIARY + FAULT SIGNALLING CONTACT - 0.5 MODULE

Caracteristici tehnice

State reporting module

Auxiliary + fault signalling contact

Enables upstream busbar connection

Indicates the position of the contacts and the fault tripping of its associated device.

To fit on the Stanga-hand side of DX3 MCBs, RCCBs, RCBOs and isolating switches

Consum: 0.236 W - 19.7 mA (12 V =)

Numar de module : 0.5

Caracteristici generale

CX³ energy management system

Conform to IEC/EN 61131-2 (Programmable controllers)

CX³ energy management system enables to measure, control and visualize the state of rail mounting protection devices (MCBs, RCCBs, RCBOs, etc...) and head equipment (DMX³ and DPX³), locally ("Stand alone") or remotely

All the module of the system are equipped with two specific communication ports: one at the backside (for communication rail) and one underneath (for communication patch cords)

Tensiune de alimentare with specific module Cat.No 4 149 45

Remote configuration possible with the help of the Energy Management Configuration Software, available for free download via E-Catalogue (giving also access to a 30-day trial version of Energy Management Software Cat.No 4 149 38/39)

Pret: 299,66 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/state-reporting-moduleule-cx3-auxiliary-fault-signalling-contact-0-5-module-235848>