

LEGRAND* SURSA STABILIZATA - THREE-PHASE - 960 W - OUTPUT 48 V= - 960 W

Caracteristici tehnice
Three-phase 960 W
Operation possible on 2 phases (80% of the nominal Putere)
Low harmonic pollution due to the integrated PFC filter
Adjustable output Tensiune
Aluminium casing
Input Tensiune: 3 x 380 to 500 V~ Output Tensiune: 48 V=
Nominal Putere : 960 W
Nominal rating : 20 A
Setting range : 48 to 55 V
Width : 110 mm
Caracteristici generale
Stabilised switched mode Putere supplies - single/two-phase and three-phase
Conforming to standards UL 508, IEC EN 60950-1 and IEC EN 61204-3
UL-approved in USA (and Canada for Cat. Nos. 1 466 54/63/82)
Operating frequency: 50/60 Hz
Output Tensiune present indicator
Potentiometer for adjusting the output Tensiune on front panel
Integrated short-circuit and overload protection
With signal or relay contact for feedback on the status of the active output Tensiune
Connection with copper conductors only
For mounting on a symmetrical rail depth 7.5 mm and 15 mm
Pret: 6.047,48 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/sursa-stabilizata-three-phase-960-w-output-48-v-960-w-236208