

LEGRAND SURSA STABILIZATA -SINGLE/TWO-PINALTIME -120-480 W -OUTPUT 24 V= -240 W

Caracteristici tehnice
Single/two-phase 120 - 480 W wide input Tensiune range
Suitable for single or two-phase networks
Also suitable for three-phase networks, when using 2 phases only
Low harmonic pollution due to the integrated PFC filter (from 240 W)
Adjustable output Tensiune
Aluminium casing
Input Tensiune: 200 to 500 V~ Output Tensiune: 24 V=
Nominal Putere : 240 W
Nominal rating : 10 A
Setting range : 24 to 28 V
Width : 63 mm
Caracteristici generale
Stabilised switched mode Putere supplies - single/two-phase and three-phase
Conforming to standards UL 508, IEC EN 60950-1 and IEC EN 61204-3
UL-approved in USA (and Canada for Cat. Nos. 1 466 54/63/82)
Operating frequency: 50/60 Hz
Output Tensiune present indicator
Potentiometer for adjusting the output Tensiune on front panel
Integrated short-circuit and overload protection
With signal or relay contact for feedback on the status of the active output Tensiune
Connection with copper conductors only
For mounting on a symmetrical rail depth 7.5 mm and 15 mm
Pret: 2.227,01 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/sursa-stabilizata-single-two-pinaltime-120-480-w-output-

24-v-240-w-236211