

# LEGRAND TRANSFORMATOR DE IZOLATIE -1 PH-PRIM 230-400 V± 15 V / SEC 230 V - 160 VA - SPRING

Caracteristici tehnice
Control and circuit isolation - spring connection
Input Tensiune = 230-400 V ± 15 V~ Output Tensiune = 230 V~
Putere in VA according to IEC and CSA : 160
Putere in VA according to UL : 140
Instantaneous admissible Putere at cos ? = 0.5 : 250
Caracteristici generale
Control, safety and circuit isolation transformers - single-phase
IP 2X or XXB up to 400 VA (coupling strip not mounted) - IP XXA over 400 VA - IK 04
Conform to IEC EN 61558-2-2 and 2-4 or 2-6, UL506 and CSA C22-2-No 66
UL USA and Canada agreements
Products suitable for building equipment conforming to standards EN 61131-2, EN 60204-1 and EN 60439-1
Active parts protected by cover up to 1000 VA
Interference filtering (except Cat.Nos 0 442 16/17/18)
Direct fixing possibility on symmetrical rail up to 250 VA
Supplied with coupling strip 0 V secondary / earth up to 1000 VA (except spring connection range)
Pret: 654,47 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/transformator-de-izolatie-1-ph-prim-230-400-v-15-v-sec-230-v-160-va-spring-236714