



**LEGRAND TRANSFORMATOR DE IZOLATIE PENTRU SPITALE - IP 00 -  
MONOFAZAT- PRIM 230 V / SEC 230 V -OUTPUT 6.3 KVA**

Caracteristici tehnice

Single-phase

Primary: 230 V~ / Secondary: 230 V~ with centre tap

Equipped with two temperature monitoring systems (bi-metal strips and thermocouple PT 100), making them compatible with any medical control system

IP 00

Output : 6.3 kVA

Terminal primary flexible cable : 35 mm<sup>2</sup>

Terminal secondary flexible cable : 35 mm<sup>2</sup>

Caracteristici generale

Isolating transformers for hospitals

Conform to standard IEC EN 61558-2-15

The main requirements of this standard, additionally to IEC 61558-2-4, concern:

secondary/earth leakage current, limited to 0.5 mA off-load

inrush current, limited to 12 times the peak value of primary current

Electrostatic shield linked to dedicated terminal

Equipped with a temperature monitoring system, and outputs on dedicated terminals

Pret: 17.293,34 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/transformator-de-izolatie-pentru-spitale-ip-00-monofazat-prim-230-v-sec-230-v-output-6-3-kva-236722>