

LEGRAND TRANSFORMATOR DE SIGURANTA - 230-400 V / 24-48 V - 1000 VA - 4 + 16 MM²

Caracteristici tehnice
Safety transformers
Conform to standard IEC EN 61558-2-6
For 63 VA transformers:
Fuse cartridges: 5 x 20 time-delayed
Fuse carrier: Cat.No 0 371 81
For 100 VA and greater transformers:
Up to 25 A : gG 10 x 38 fuse cartridges and fuse carrier Cat. No. 0 058 08
From 25 A to 50 A : gG 14 x 51 fuse cartridges and fuse carrier Cat.No 0 215 01
From 50 A upwards : gG 22 x 58 fuse cartridges and fuse carrier Cat.No 0 216 01
C curve MCBs
Input Tensiune = 230-400 V~ Output Tensiune = 24-48 V~
Putere : 1000 VA
Primary terminal flexible cable : 4 mm²
Secondary terminal flexible cable cross-section : 16 mm²
Caracteristici generale
Transformers and auto-transformers IP 55 - class II - single-phase
Pret: 4.243,35 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/transformator-de-siguranta-230-400-v-24-48-v-1000-va-4-16-mm2-236785