

LEGRAND TRANSFORMATOR MONOFAZAT - PRIM 230-400 V / SEC 115-230 V - 220 VA

Caracteristici tehnice
Circuits isolation
Input Tensiune = 230-400 V~ Output Tensiune = 115-230 V~
Putere : 220 VA
Primary terminal flexible cable : 1 to 4 mm²
Secondary terminal flexible cable : 1 to 4 mm²
Caracteristici generale
Equipment transformers - single-phase
IP 2X or XXB up to 450 VA - up to 310 VA in 12-24 V - (coupling strip not mounted) - IK 04
Clip on fixing possibility up to 160 VA with accessories Cat.No 0 044 16 or 0 428 99
Transformers with 2 secondary Tensiune supplied with coupling strip
Transformers up to 450 VA supplied with isolated strip for 0 V connection secondary / earth (except Cat.No 0 428 46)
Conform to IEC EN 61558-2-6 for 12 V, 24 V and 48 V and conform to IEC EN 61558-2-4 for 115 V and 230 V
Products suitable for building equipment conforming to standards EN 61131-2, EN 60204-1 and EN 61 439-1
Pret: 731,70 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/transformator-monofazat-prim-230-400-v-sec-115-230-v-220-va-236805