



LEGRAND TRANSFORMATOR MONOFAZAT - PRIM 230-400 V / SEC 115-230 V - 220 VA

Caracteristici tehnice

Circuits isolation

Input Tensiune = 230-400 V~ Output Tensiune = 115-230 V~

Putere : 220 VA

Primary terminal flexible cable : 1 to 4 mm²

Secondary terminal flexible cable : 1 to 4 mm²

Caracteristici generale

Equipment transformers - single-phase

IP 2X or XXB up to 450 VA - up to 310 VA in 12-24 V - (coupling strip not mounted) - IK 04

Clip on fixing possibility up to 160 VA with accessories Cat.No 0 044 16 or 0 428 99

Transformers with 2 secondary Tensiune supplied with coupling strip

Transformers up to 450 VA supplied with isolated strip for 0 V connection secondary / earth (except Cat.No 0 428 46)

Conform to IEC EN 61558-2-6 for 12 V, 24 V and 48 V and conform to IEC EN 61558-2-4 for 115 V and 230 V

Products suitable for building equipment conforming to standards EN 61131-2, EN 60204-1 and EN 61 439-1

Pret: 724,96 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/transformator-monofazat-prim-230-400-v-sec-115-230-v-220-va-236805>