



LEGRAND UNIVERSAL VARIATOR MOSAIC - CUOUT NEUTRAL - ALU - 2 MODULE

Caracteristici tehnice

Dimmer switches 110-230 V~ 50 Hz

Can be remotely controlled via non-illuminated pushbuttons, with each pushbutton able to perform the dimming function

When switched on, lighten at the level set before last switched off

For installation in Montaj incastrat box depth 40 mm min

Universal dimmer without neutral, 2-wire

For all types of lamps:

dimnable LEDs: 5 W to 75 W (10 lamps max.)

dimnable compact fluorescent lamps: 5 W to 75 W (10 lamps max.)

halogen with ferromagnetic or electronic transformer: 3 VA to 400 VA

fluorescent tube - ballast: 3 VA to 200 VA

halogen and incandescent 230 V: 3 W to 400 W

When switched on, gradually (2 seconds) lights up at the level set before last switch-off

Functionning:

dimming mode

pre-set level mode (0%, 33%, 66%, 100%)

nightlight mode: dimming down of the lamp for
1 hour

2 module

Alu

Caracteristici generale

Mosaic™ Programme mechanisms - dimming control

Pret: 356,70 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/universal-variator-mosaic-cuout-neutral-alu-2-module-237081>