

LEGRAND UNIVERSAL VARIATOR MOSAIC - CUOUT NEUTRAL - ALU - 2 MODULE

Caracteristici tehnice
Dimmer switches 110-230 V~- 50 Hz
Can be remotely controlled via non-illuminated pushbuttons, with each pushbutton able to perform the dimming function
When switched on, lighten at the level set before last switched off
For installation in Montaj incastrat box depth 40 mm min
Universal dimmer without neutral, 2-wire
For all types of lamps:
dimmable LEDs: 5 W to 75 W (10 lamps max.)
dimmable compact fluorescent lamps: 5 W to 75 W (10 lamps max.)
halogen with ferromagnetic or electronic transformer: 3 VA to 400 VA
fluorescent tube - ballast: 3 VA to 200 VA
halogen and incandescent 230 V: 3 W to 400 W
When switched on, gradually (2 seconds) lights up at the level set before last switch-off
Functionning:
dimming mode
pre-set level mode (0%, 33%, 66%, 100%)
nightlight mode: dimming down of the lamp for
1 hour
2 module
Alu
Caracteristici generale
Mosaic™ Programme mechanisms - dimming control
Pret: 368,72 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/universal-variator-mosaic-cuout-neutral-alu-2-module-237081