

LEGRAND VOLTAGE SURGE PROTECTOR MOSAIC -16 A -250 V~ -50/60 HZ -L MAX 6 KA -2 MODULE -ALB

Caracteristici tehnice
Tensiune surge protector
16 A - 250 V~ - 50/60 Hz
Protection against overTensiunes of atmospheric or industrial origin, in an installation already protected by a Tensiune surge protector in the panel
For installation downstream of an RCBO, protects all the sockets wired in cascade with the Tensiune surge protector
Operation displayed by indicator light
Keeps the socket energised after an overTensiune (mains or lightning strike) until replacement of module
Cat.No 0 775 41
Nominal discharge current (In): 1.5 kA
Maximum permissible current (Imax): 6 kA
Protection level (Up): L-N: 1 kV; N-PE: 1 kV
Open circuit Tensiune (Uoc): 3 kV
Conform to standards EN 61643-11
White
2 module
Caracteristici generale
Mosaic™ Programme mechanisms - Tensiune surge protector, replacement module, buzzers, bells, blanking plates, cable outlets and proximity MCBs
Pret: 626,40 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/voltage-surge-protector-mosaic-16-a-250-v-50-60-hz-l-max-6-ka-2-module-alb-237288