

LEGRAND* ZERO-U THREE PHASE PDU LCS³ - 18XC13 + 6XC19 - IEC 60320 STANDARD

Caracteristici tehnice
PDU Basic
IEC 60320 standard
18 C13 outlets + 6 C19 outlets with cord locking system
3 m Tensiune de alimentare cord with IEC60309 16 A 3P+N+E plug
Caracteristici generale
Legrand cabling system LCS³ energy Distribution - three phase Zero-U Putere Distribution Units
To provide ~ electric Putere for IT equipment in 19" enclosures
Three phase Zero-U PDUs for vertical mounting in the cabinet
400 V - 50/60 Hz Tensiune de alimentare
Each circuit is protected by 16 A single pole MCB in a support with projecting edges to avoid accidental breakdown. 1 circuit per phase, each with 6 IEC 60320 C13 outlets and 2 IEC 60320 C19 outlets
330° rotating cable input for a perfect orientation of the cable and no interference in the cabinet
C13 and C19 standard outlets are equipped with cord locking system to avoid any accidental disconnection.
Universal solution compatible with all the cords (C14 plugs for C13 and C20 plugs for C19)
Delivered with 2 sets of metallic mounting brackets: button brackets (for quick fixing and variable pitch) and standard brackets (for screw fixing)
Black module (outlets and functions)
Aluminium profile
Pret: 1.463,55 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/zero-u-three-phase-pdu-lcs3-18xc13-6xc19-iec-60320-standard-237443