



SCHRACK DEVO PRO II 27W 3800LM 840 230V ECG IP66 CL 1 PMMA 1200MM

EAN-Code 9004840487879

Lungime 1200,00mm

Lungime net? 86,00mm

Inaltime 95,00mm

Mas? net? 2,24kg.

CLAS? ENERGIE C

Temperatura minim? a mediului ambient -20°C

Temperatura maxim? a mediului ambient 35°C

Tip iluminare downlight, pendulum luminaire, wall luminaires

Montaj Montaj de perete, Montaj incastat in plafon, Pendul

Culoare gri deschis

Material Glass fibre reinforced polyester

Masc? PMMA opal

Fabricant 01-Schrack-Trinity

Balast LED driver

Tensiune de alimentare AC 230V

Dulie lamp? LED Platine

Watt 27W/23W/34W/37W

Eficien?? sistem 141lm/W

Culoare lumin? neutral white

Temperatura culorii 4000K

Indice redare culoare ?80

Lumeni 3700lm/3200lm/4700lm/5200lm

Durat? de via?? 50.000h / L70 / B50

Dimabil nu

Clas? de protec?ie I

Grad de protec?ie IP66

Clas? energetic? C

Rezisten?a la ?oc IK03

Surse de lumin? incluse da

Fire protection marking D

Numbers of luminars per MCB B10 22

Numbers of luminars per MCB B13 27

Numbers of luminars per MCB B16 34

Numbers of luminars per MCB B20 42

Numbers of luminars per MCB B25 53

Numbers of luminars per MCB C10 33

Numbers of luminars per MCB C13 45

Numbers of luminars per MCB C16 54

Numbers of luminars per MCB C20 70

Numbers of luminars per MCB C25 88

Pachete disponibile 1 buc., 72 buc.

Pret: 353,20 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/devo-pro-ii-27w-3800lm-840-230v-ecg-ip66-cl-1-pmma-1200mm-261035>