



SCHRACK DEVO PRO II 28W 840 230V ECG EK-KIT 3H IP66 CL 1 L-1200MM

EAN-Code 9004840882919

Lungime 1200,00mm

Lungime net? 86,00mm

Inaltime 95,00mm

Mas? net? 2,24kg.

Temperatura minim? a mediului ambient -20°C

Temperatura maxim? a mediului ambient 35°C

Tip iluminare downlight, pendulum luminaire, wall luminaires

Montaj Montaj de perete, Montaj incastat in plafon, Pendul

Culoare gri deschis

Material Glass fibre reinforced polyester

Mas? PC opal

Fabricant 01-Schrack-Trinity

Balast LED driver

Tensiune de alimentare AC 230V

Dulie lamp? LED Platine

Watt 28W

Culoare lumin? neutral white

Temperatura culorii 4000K

Indice redare culoare ?80

Lumeni 3400lm

Iluminat de siguran?? Emergency kit 3h

Flux luminos in mod emergen?? 400lm

Durat? de via?? 50.000h / L70 / B50

Dimabil nu

Clas? de protec?ie I

Grad de protec?ie IP66

Rezistența la șoc IK03

Surse de lumină incluse da

Fire protection marking D

Numbers of luminaires per MCB B10 20

Numbers of luminaires per MCB B13 25

Numbers of luminaires per MCB B16 32

Numbers of luminaires per MCB B20 40

Numbers of luminaires per MCB B25 50

Numbers of luminaires per MCB C10 30

Numbers of luminaires per MCB C13 41

Numbers of luminaires per MCB C16 50

Numbers of luminaires per MCB C20 65

Numbers of luminaires per MCB C25 81

Pachete disponibile 1 buc.

Pret: 928,98 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/devo-pro-ii-28w-840-230v-ecg-ek-kit-3h-ip66-cl-1-l-1200mm-261036>