



SCHRACK FI?? CEE, 5 POLI 16A 400V IP44, QUICK CONNECTION

EAN-Code 9004840842647

Lungime 132,00mm

L??ime net? 73,00mm

Adancime net? 65,00mm

Mas? net? 0,19kg.

disipare 1,00W

Curent nominal 16A

Poli 5

Configuratie contacte 3P+N+PE

Grad de protec?ie IP44

Cod de culoare rosu

Pozi?ia contactului de protec?ie la p?mant 6h

Tensiunea de func?ionare nominal? 230/415V

Stabilitate la tensiune de izola?ie 690V

Frecven?? 50/60Hz

Material PA6, PC/ABS

Material de contact Alam?

Tip conexiune Cleme elastice

Standard EN 60309-1, EN 60309-2

Sec?iune minim?, conductor solid 1mm²

Sec?iune maxim?, conductor solid 2,50mm²

Sec?iune minim?, conductor flexibil 1,50mm²

Sec?iune maxim?, conductor flexibil 2,50mm²

Diametru maxim conductor 16,50mm

Lungime de dezizolare L/N 20mm

Lungime de dezizolare PE 20mm

Rezisten?a la fir incins 650°C

Pachete disponibile 1 buc., 100 buc.
Pret: 44,54 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/fisa-cee-5-poli-16a-400v-ip44-quick-connection-262830>