



SCHRACK KARO II LED, 32W, 2560LM, 3000K, IP44, 230V, 120°

EAN-Code 9004840862638, 9004840862676

In?ime 115,00mm

Diametru 410,00mm

Mas? net? 1,45kg.

Temperatura minim? a mediului ambient -20°C

Temperatura maxim? a mediului ambient 40°C

Tip iluminare downlight, wall luminaires

Montaj Montaj de perete, Montaj incastat in plafon

Culoare alb

Material tabl? de o?el

Masc? PMMA opal

Fabricant 01-Schrack-Trinity

Unghiul de radia?ie 120°

Balast LED driver

Tensiune de alimentare AC 220-240V

Dulie lamp? LED Platine

Watt 32W

Eficien?? sistem 77lm/W

Culoare lumin? alb cald

Temperatura culorii 3000K

Indice redare culoare ?80

Stabilitatea culorii MacAdam

Lumeni 2560lm

Durat? de via?? 45.000h / L70 / B50

Dimabil nu

Clas? de protec?ie I

Grad de protec?ie IP44

Rezistența la șoc IK02

Surse de lumină incluse da

Numbers of luminars per MCB B10 40

Numbers of luminars per MCB B13 50

Numbers of luminars per MCB B16 65

Numbers of luminars per MCB B20 80

Numbers of luminars per MCB B25 100

Numbers of luminars per MCB C10 40

Numbers of luminars per MCB C13 50

Numbers of luminars per MCB C16 65

Numbers of luminars per MCB C20 80

Numbers of luminars per MCB C25 100

Pachete disponibile 1 buc., 5 buc.

Pret: 155,19 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/karo-ii-led-32w-2560lm-3000k-ip44-230v-1200-266201>