



SCHRACK PRIMOLUX LED 1235 38W 4050LM/840 3H M OPAL ECG IP44 WHITE

EAN-Code 9004840571448

Lungime 1235,00mm

Lungime net? 95,00mm

Inaltime 72,00mm

Mas? net? 3,20kg.

Temperatura minim? a mediului ambient 0°C

Temperatura maxim? a mediului ambient 30°C

Tip iluminare downlight

Montaj Montaj incastat in plafon

Culoare alb

Material PMMA opal, tabl? de o?el

Masc? opal

Fabricant 01-Schrack-Trinity

Balast LED driver

Tensiune de alimentare AC 220-240V

Dulie lamp? LED Platine

Watt 38W

Eficien?? sistem 118lm/W

Culoare lumin? neutral white

Temperatura culorii 4000K

Indice redare culoare ?80

Lumeni 4500lm

Iluminat de siguran?? Emergency kit 3h

Flux luminos in mod emergen?? 370lm

Durat? de via?? 60.000h / L80 / B10

Dimabil nu

Clas? de protec?ie I

Grad de protecție IP44
Rezistența la șoc IK05
Surse de lumină incluse da
Pachete disponibile 1 buc.
Pret: 1.855,13 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/primolux-led-1235-38w-4050lm-840-3h-m-opal-ecg-ip44-white-272685>