Image not found or type



ZALUX LAMPA LINIARA ETANSA CU FIXARE RAPIDA BHE 69K 1.2 40-840 ET BPM 3M

Gas-tight, long-lasting, compact and resistant luminaire with easy installation
Single-part IP66 / IP69K extruded PMMA profile, up to 138lm/W and flicker free.
Gas tight: hermetically sealed against liquid and gas income.
PWIS-free to guarantee a perfect finish in paint shops and coating areas.
Quick and safe mounting with no tools needed.
Extraordinary chemical resistance.
Downloads
Features
Mechanical
Profile Extruded PMMA with UV protection, upper part grey RAL 7035, bottom part opal
End caps Acrylonitrile styrene acrylate (ASA)
Gasket PWISS-free silicone
Cable entry Cable gland with external cable
Fixing clips Stainless steel
Operational Data
Light colour 4,000 K
CRI >80
Luminous flux 4,000 lm
Power 29 W
Efficiency 135 lm/W
Functional
Lifetime L80 70,000 Custom.U1 at 25°C
Fire protection GRP and PMMA / Flammability (UL94): HB
Glow wire test (EN 60695-2-11): 650ºC
Electrical
Driver non dimmable

Connection External cable 3m
Flicker factor < 1%
Power factor > 0.95 full load
Photometrical
Colour consistency < 3 SDCM
Dimensions
Length (X) 1,200 mm
Distance between springs (Xm) 800 mm
Width (Y) 76 mm
Height (Z) 67 mm
Weight 2 kg
<span class="elementor-button-text"
Pret: 528,04 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/lampa-liniara-etansa-cu-fixare-rapida-bhe-69k-1-2-40-840-et-bpm-3m-287553