



## **ZALUX LAMPA LINIARA TIP FIPAD DHE 1.5 100-840 ET SMC DPM IX CG**

Linear openable high bay

Up to 170lm/W.

Up to 50°C.

Chemical resistant.

Up to 15,000lm under request for the higher installations.

Downloads

Features

Mechanical

Housing Compressed fibreglass reinforced polyester (GRP), grey RAL 7035

Diffuser Injected PMMA with UV protection, frosted finish

Gasket Polyurethane

Cable entry Cable gland

Closing clips Stainless steel

Fixing clips Stainless steel

Operational Data

Light colour 4,000 K

CRI >80

Luminous flux 10,000 lm

Power 59 W

Efficiency 170 lm/W

Functional

Lifetime L80 100,000 h at 35°C

Fire protection GRP and PMMA / Flammability (UL94): HB

Glow wire test (EN 60695-2-11): 650°C

Electrical

Driver non dimmable

Connection 3 pole push wire terminal block

Flicker factor < 1%

Power factor > 0.95 full load

Photometrical

Colour consistency < 3 SDCM

Dimensions

Length (X) 1,573 mm

Distance between springs (Xm) 1,100 mm

Width (Y) 101 mm

Height (Z) 84 mm

Weight 2.3 kg

<span class="elementor-button-text"

Pret: 574,66 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/lampa- liniara-tip-fipad-dhe-1-5-100-840-et-smc-dpm-ix-cg-287579>