www.MATERIALE ELECTRICE.ro
Consiliere specializata

Image not found or type



ZALUX LAMPA LINIARA TIP FIPAD DHE+ 1.2 40-840 ET SMC DPM IX CG

High performance with optional wireless Bluetooth control
Up to 160lm/W and 50ºC with high chemical resistance.
100,000 hours lifetime to contribute to installation profitability.
With internal diffuser to avoid direct contact with LED module.
Optional presence and daylight sensors to optimize the use of the light.
Downloads
Features
Mechanical
Housing Compressed fibreglass reinforced polyester (GRP), grey RAL 7035
Diffuser Injected PMMA with UV protection, frosted finish
Gasket Polyurethane
Cable entry Cable gland
Closing clips Stainless steel
Fixing clips Stainless steel
Operational Data
Light colour 4,000 K
CRI >80
Luminous flux 4,000 lm
Power 25 W
Efficiency 160 lm/W
Functional
Lifetime L80 100,000 h at 35°C
Fire protection GRP and PMMA / Flammability (UL94): HB
Glow wire test (EN 60695-2-11): 650ºC
Electrical
Driver non dimmable
Connection 3 pole push wire terminal block

Flicker factor < 1%
Power factor > 0.95 full load
Photometrical
Colour consistency < 3 SDCM
Dimensions
Length (X) 1,277 mm
Distance between springs (Xm) 800 mm
Width (Y) 101 mm
Height (Z) 84 mm
Weight 1.8 kg
<span class="elementor-button-text"
Pret: 407,06 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/lampa-liniara-tip-fipad-dhe-1-2-40-840-et-smc-dpm-ix-cg-287587