www.MATERIALE ELECTRICE.ro
Consiliere specializata

Image not found or type



ZALUX LAMPA PENTRU MEDII HIPERCLORURATE SI ÎN AER LIBER STRONGERTUBE G2 B 6500-840 ET PMMA ZB

For hyper chlorinated environments and outdoor
Specific potting for a full tight sealing to avoid the penetration of gases and water.
Safe against the corrosion of LED modules and electronic compo-nents.
High thickness PMMA resistant to chemicals and robust for a durable use in outdoor.
End caps with great thermal stability to resist UV radiation, heat, water, ageing and chemicals.
Downloads
Features
Mechanical
Profile High thickness PMMA
End caps Acrylonitrile styrene acrylate (ASA)
Gasket Polyurethane
Cable entry Cable gland with external cable
Fixing clips Specific stainless steel fixing brackets
Operational Data
Light colour 4,000 K
CRI >80
Luminous flux 6,500 lm
Power 43 W
Efficiency 150 lm/W
Functional
Lifetime L80 100,000 h at 35°C
Fire protection PMMA / Flammability (UL94): HB
Glow wire test (EN 60695-2-11): 650ºC
Electrical
Driver non dimmable
Connection 3 pole push wire terminal block

Flicker factor < 1%
Power factor > 0.95 full load
Photometrical
Colour consistency < 3 SDCM
Dimensions
Length (X) 1,340 mm
Distance between springs (Xm) 1,205 mm
Width (Y) 112 mm
Height (Z) 112 mm
Weight 4.6 kg
<span class="elementor-button-text"
Pret: 1.141,67 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/lampa-pentru-medii-hiperclorurate-si-in-aer-liber-strongertube-g2-b-6500-840-et-pmma-zb-287797