



ZALUX LAMPA IP66 IK08 ZALEDA EVOL G2 4000-840 ET PC

High protection for indoor and outdoor applications
Wide temperature range, suitable from cold storage to heavy industries.
Excellent thermal management for use in tough environments.
Safe for outdoor, with theft protection.
Plug and play for tool-less, fast and easy installation.

Downloads

Features

Mechanical

Housing Die-cast aluminium alloy EN-47100, dark grey RAL DB703

Diffuser Injected polycarbonate with UV protection, opal finish

Gasket Polyurethane

Fixing clips Stainless steel

Operational Data

Light colour 4,000 K

CRI >80

Luminous flux 4,400 lm

Power 27 W

Efficiency 163 lm/W

Functional

Lifetime L80 85,000 h at 35°C

Fire protection PC / Flammability (UL94): V2

Glow wire test (EN 60695-2-11): 850°C

Electrical

Driver non dimmable

Connection Stucchi Fast Connector

Flicker factor < 1%

Power factor > 0.95 full load

Photometrical

Colour consistency < 3 SDCM

Dimensions

Length (X) 1,047 mm

Distance between springs (Xm) 492 mm

Width (Y) 95 mm

Height (Z) 105 mm

Weight 2.9 kg

<span class="elementor-button-text"

Pret: 0,00 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/lampa-ip66-ik08-zaleda-evol-g2-4000-840-et-pc-287860>