

IEK AUTOMAT DE SCARA TO47 16A 230V PENTRU DIN-RAIL

These devices are intended for automated shutting down/switching on the lighting of staircase landings, corridors or other objects within a pre-defined time period (from 1 to 7 min). TO-47 is applied in lighting circuits up to 3,5 kW and is intended for using with incandescent and halogen lamps.Setting the preset time pre-defined time period (from 1 to 7 min).Nominal voltage of load circuit: 230
Type of control voltage 1: EV000460
Width in number of modular spacings: 1
Max. cross section incoming cable: 0,75...4,0
Frequency: 50
Mounting method: EV000242
Built-in depth: 68
Number of normally open contacts: 0
Number of normally closed contacts: 1
Number of change-over contacts: 0
Number of contacts as change-over contact: 0
Rated switch current: 16
Release-delay: 1-7
Wiring system: EV005720
Pre-warning of switching-off: EV000494
Repetitive: EV005725
Supply voltage: 230
Voltage type of supply voltage: EV000460
Max. load fluorescent lamp: 10
Delay-on energization time: < 1
Time Delay Setting Step: 0,5
Output current to external control button: ? 50
Mechanical wear resistance: 10

Electric wear resistance: 1
Height: 86
Ambient temperature: -25...+50
Control voltage 1: ?????????? (AC)
Number of contacts as normally closed contact: 1
Number of contacts as normally open contact: 0

Pret: 83,40 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/lighting-time-delay-selector-to47-16a-230v-pentru-din-rail-307443