

IEK TRANSPENTRUMATOR REDUCTOR DE CURENT TSHP-0,66 2000/5A 15BA CLASS 0,5 SIZE 100

The TShP-0,66 current transformers are designed for: – use in electric energy metering circuits for accounts with the customers; – use in electric energy revenue metering circuits; – output of a signal for measurement instruments or protection and control devices.The cores of all TOP-0.66 and TShP-0.66 transformers are made from special steel of transformer grade with increased content of silicon that enables extending of recalibration interval.
The copper tinned bus of ??P-0.66 transformer allows for connection of copper and aluminum conductors.
The enclosures of all TOP-0.66 and TShP-0.66 transformers are made from self-extinguishing plastic.
The recalibration interval is 4 years.
Each transformer is completed with a cover for secondary terminals, fixtures for panel installation and bus fixing, color labels for phase indication.
Small weight and size allow for considerable saving of place in a cabinet.Model: EV009515
Primary rated current: 2000
Secondary rated current: 5
Accuracy class: 0,5
Accuracy class: 0,5
Secondary rated apparent power: 15
Secondary connection: EV000415
Max operating voltage: 0,72
Nominal frequency: 50
Suitable for maximum cable diameter: 60
Nominal voltage: 660
Pret: 165,48 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/transpentrumator-reductor-de-curent-tshp-0-66-2000-5a-15ba-class-0-5-size-100-307845