

IEK BUSBAR BUSBAR PRIZA TYPE 1P 100A (1 M)

Bridging bars are applied for convenient and safe connection of various groups: VA (MCBs), AD (RCBOs), VD (RCCBs) and VN (modular disconnectors). Buses with 18mm step are intended for commuting one-modulefold wide equipment; 27 mm step buses are designed for 1,5 module-fold wide devices. Buses are optimized per rated current of 100 A but can be used with rated current of 125 A if the incoming switch is connected on the center. There are plugs intended for 1,5 module wide buses.Made of copper plates and placed in a plastic insulating flame-retardant housing.
Can be used with a rated current of 125A, if the input machine is connected in the center.Maximum number of connected devices: 54
Pitch dimensions: 18
Cross section: 78
Length: 1000
Rated permanent current Iu: 100
Type of electric connection: EV000197
Rated surge voltage: 4
Rated short-time withstand current Icw: 15
Height: 30.5
Width: 4.2
Number of poles (total): 1
Nominal voltage: 230/400
Weight: 0,2
Ambient temperature: -45...+40
Rated insulation voltage Ui: 600
Number of phases: 1
Pret: 153,85 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/busbar-busbar-priza-type-1p-100a-1-m-308755