www.MATERIALE ELECTRICE.ro
Consiliere specializata



IEK DISTRIBUITOR PENTRU DIN-RAIL RBD-250A

RBD distribution terminal blocks are designed for use as terminal clamps when multiple smaller conductors must be connected to a conductor with bigger cross-section, for arrangement of distribution systems in cabinets, arrangement of main earthing busbar. Intended for installation on DIN rail or mounting panel both in power supply cabinets and flat distribution boards, working in the systems of voltages up to 1000 V and frequency 50 Hz, at ambient air temperature from -40 to +70 C. RBD distribution terminal blocks are made from high-quality brass with special protective coating. The body is made from non-combustible plastic. Installation methods: - on DIN rail 35 mm wide; - on the board panel using 2 screws.Made of tinned copper, the housing is made of flame-retardant plastic, having excellent electrical insulating properties.Number of poles: 1
Connection type: EV000766
Number of connections < 6 mm²: 0
Number of connections 10 mm²: 4
Number of connections 16 mm²: 5
Number of connections 25 mm²: 0
Number of connections > 25 mm²: 3
Number of connections total: 12
Mounting method: EV010333
Height: 96.0
Width: 48.0
Depth: 51.0
Nominal current: 250
Frequency: EV008013
Nominal voltage: 1000
Max medium-radar short current Icw: 24.5
Nomin withstand pulse current Ipk: 51
Degree of protection (IP): EV006405
Section of conductors connections at the input: 1?120

Section of conductors connections at the outlet: 5?16; 2?35; 4?10
Material housing: EV000139
Material contact: EV000149
Ambient temperature: -40...+70
Pret: 138,69 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/distribuitor-pentru-din-rail-rbd-250a-308761