www.MATERIALE ELECTRICE.ro
Consiliere specializata



IEK INPUT TERMINAL PENTRU KVM MODULAR EQUIPMENT 4-25MM2 (DIRECT INPUT)

Used to connect conductors to modular equipment. Central connection of conductors.Convenient connection of conductors to terminal clamps of modular devices when using connecting buses.
The flat terminal output provides reliable electrical contact with the connecting bus terminal.
Possibility of summing up conductors of large cross-section up to 25 mm2.Connectable conductor cross section solid-core: 4…25
Connectable conductor cross section multi-wired: 4…25
Rated current In: 100
Nominal rated voltage: 400
Type of electrical connection 2: EV000415
Connection position: EV000644
Number of poles: 1
Number of clamp positions per pole: 1
Mounting method: EV005276
Material insulation body: EV000139
Operation temperature: -40...+50
Inflammability class of insulation material acc. with UL94: EV004430
Width/grid dimension: 17.0
Length: 32,5
Colour: EV000270
Nominal operating AC voltage Ue: 400
Nominal DC operating voltage Ue: 220
Nominal frequency: 50
Rated insulation voltage Ui: 415
Max. conductor cross section: 25
Material clamp: EV000149
Material housing: EV000139

Ambient class: IEK_V0000009
Width: 17
Height: 19
Nominal Attachment Capacity: 4...25
Tightening torque Nm at conductor section: 2,5
Quantity in the kit: 100
Model: EV005828
Minimum section: 16.0
Attachment screw: ?8
Current-carrying part material: EV000138
Type of electrical connection 1: EV000415
Pret: 7,73 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/input-terminal-pentru-kvm-modular-equipment-4-25mm2-direct-input-308968