

IEK BUSBAR PIN TYPE 4P 100A STEP 27 MM (1 M)

Bridging bars are applied for convenient and safe connection of various groups: VA (MCBs), AD (RCBOs), VD (RCCBs) and VN (modular disconnectors). Buses with 18mm step are intended for commuting one-modulefold wide equipment; 27 mm step buses are designed for 1,5 module-fold wide devices. Buses are optimized per rated current of 100 A but can be used with rated current of 125 A if the incoming switch is connected on the center. There are plugs intended for 1,5 module wide buses.Made of copper plates and placed in a plastic insulating flame-retardant housing.
Can be used with a rated current of 125A, if the input machine is connected in the center.Maximum number of connected devices: 36
Pitch dimensions: 27
Cross section: 807
Length: 1000
Rated permanent current Iu: 100
Type of electric connection: EV000158
Rated surge voltage: 4
Rated short-time withstand current Icw: 17
Height: 46.2
Number of poles (total): 4
Nominal voltage: 230/400
Weight: 1
Ambient temperature: -45...+40
Rated insulation voltage Ui: 600
Number of phases: 4
Pret: 503,77 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/busbar-pin-type-4p-100a-step-27-mm-1-m-309211