



IEK CLEMA ZNI-6PEN 6MM2 (JXB-GROUNDING)

These terminal blocks serve for safe and compact connection of phase, neutral and protective (ground) conductors of various size. They are installed onto a DIN-rail. The set is completed with a marking band for number inscription and side blinds for ZNI series screw terminal blocks. Color: blue, gray, green. Terminal clamps can be covered with plastic blinds of correspondent size and color. They are made of colored non-inflammable polyamide of yellowish-green (grounding), blue (neutral), gray and green (phase) color. The set is completed with a marking band for number inscription.

They are made of colored non-inflammable polyamide. Connectable conductor cross section solid-core: 0,5...10

Connectable conductor cross section multi-wired: 0,5...6

Rated current In: 50

Nominal rated voltage: 600

Type of electrical connection 2: EV000415

Connection position: EV001224

Number of poles: 1

Number of clamp positions per pole: 2

Mounting method: EV005503

Material insulation body: EV000402

Operation temperature: -40...+80

Inflammability class of insulation material acc. with UL94: EV004429

Width/grid dimension: 9.0

Length: 40,5

Colour: EV000120

Nominal operating AC voltage Ue: 600

Nominal DC operating voltage Ue: 440

Nominal frequency: 50

Rated insulation voltage Ui: 660

Max. conductor cross section: 6

Material clamp: EV000179
Material housing: EV000402
Ambient class: IEK_V0000009
Degree of protection (IP): EV006405
Width: 9,0
Height: 57,5
Nominal Attachment Capacity: 2,5...6
Model: IEK_V0000472
Type of electrical connection 1: EV000415
Pret: 5,39 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/clema-zni-6pen-6mm2-jxb-grounding-309454>