



IEK ANCHOR BRIDA S ZAB 16-25 (PA25X100)

ZAB anchor clamps are designed for anchoring of 2 or 4 user's self-bearing insulated wires. Special surface geometry of wedges ensures safe fixing of conductor, preventing it from falling out, without damage to the wire insulation. All parts are made from polymers, resistant to UV radiation and weather conditions. ZAB 16-25 clamp does not require tools for installation and its quick-detachable bail allows for fastening to the brackets and hooks. Bail length varies from 90 to 150 mm and it has an additional latch preventing loosening from wedge holder, for example, under effect of increased wind load. ZAB 16-25 clamp does not require tools for installation and its quick-detachable bail allows for fastening to the brackets and hooks. Bail length varies from 90 to 150 mm and it has an additional latch preventing loosening from wedge holder, for example, under effect of increased wind load. Section of retained SIP: 2?16...4?25

Weight: 0,09

Nominal voltage: 1000

Ambient class: IEK_V0000007

Ambient temperature: -60...70

Clamping cable diameter: 7,2...8,7

Number of cables: 2 ??? 4

Material: EV007763

Surface protection: EV000154

Max. tensile load: 1961

Minimum destructive load: 1,9

Width: 56 ± 1

Height: 43 ± 1,5

Pret: 15,56 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/anchor-brida-s-zab-16-25-pa25x100-310264>