www.MATERIALE ELECTRICE.ro
Consiliere specializata



IEK KOPM1500 SUSPENSION BRIDA S ECOLINE

Suspension supporting clamps are intended for fastening the insulated carrying neutral SSIC under 1kW. The neutral is fixed with an adjustable clamp. ZPN 2000 clamps allow fastening them on hooks up to 24 mm in diameter. Sliding joints contribute to the clamps moving transversely and longitudinally. A set of intermediate suspension KOPM 1500 represents a bracket with a projection in the top part preventing the clamp from moving into the upper position. The bracket has a hole for its fastening to the bearing with anchor screws. There is a possibility to fix it to bearings with the help of a rim band. To facilitate the band amounting process, the bracket is supplied with separating facets. KOPM 1500 is made of corrosion-resistant aluminum alloy in set with a separately delivered ZPN 1500 suspension clamp made of polymer strengthened with a fiber glass structure resistant to UV and weather conditions.A set of intermediate suspension KOPM 1500 represents a bracket with a projection in the top part preventing the clamp from moving into the upper position. The bracket has a hole for its fastening to the bearing with anchor screws.
There is a possibility to fix it to bearings with the help of a rim band.
To facilitate the band amounting process, the bracket is supplied with separating facets.
KOPM 1500 is made of corrosion-resistant aluminum alloy in set with a separately delivered ZPN 1500 suspension clamp made of polymer strengthened with a fiber glass structure resistant to UV and weather conditions.Ultimate load: 9000
Material: EV000154
Ambient temperature: -60...+70
Type of fastening: EV007463
Connection type construction part: EV000137
Thread size metric (M..): -
Flange thickness: -
Tube/cable diameter: 4,50…10,96
Weight: 0,453
Neutral bearing section: 16...95
Neutral bearing diameter: 8...15
Pret: 65,30 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/kopm1500-suspension-brida-s-ecoline-310281