



### **IEK SUSPENSION BRIDA S ZPS 2X25-4X120/1800/30 (SO130.02)**

Suspension clamps of ZPS series are intended for hanging self-supporting insulated cable systems under 1 kW on intermediate supports. They also can be used for SSIC with insulated carrier neutral. ZPS clamps can be applied on angle support up to 90°. These clamps are made of hot-dip galvanized steel, their plastic elements – from polymers resistant to UV and weather conditions. These factors ensure the operability of devices within 40 years. The clamps are supplemented with breakaway bolts ensuring a secured fixation of conductors inside them. Also in case of necessity the devices can be dismantled owing to the fact that the bolt heads are dismantable. These clamps are made of hot-dip galvanized steel, their plastic elements – from polymers resistant to UV and weather conditions.

These factors ensure the operability of devices within 40 years. The clamps are supplemented with breakaway bolts ensuring a secured fixation of conductors inside them. Also in case of necessity the devices can be dismantled owing to the fact that the bolt heads are dismantable. Ultimate load: 18

Section area of SIP conductors: 25...120

Material: EV000179

Surface protection: EV000254

Nominal voltage: 1000

Ambient temperature: -60...+70

Type of fastening: EV007463

Connection type construction part: EV003906

Thread size metric (M.): 8

Flange thickness: -

Tube/cable diameter: 2?25...4?12,28

Moment of screw head failure during installation: 10

Width: 78 ± 2

Height: 131 ± 3

Weight: 0,334

Pret: 66,23 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/suspension-brida-s-zps-2x25-4x120-1800-30-so130-02-310331>