

IEK GIA 06-16 BUSHINGS PENTRU SELF-SUPPORTING INSULATED CONDUCTOR S WITH A CARRYING NEUTRAL (MJPB 06-16)

GIA bushings for self-carrying wires serve for mechanical and electrical connection of self-supporting wires. Admitted mechanical stress on the crimped connection for carrying wires makes up 40% of its tensile strength when connected to a SSIC wire and 20% in case of copper wire crimping.GIA bushings for self-carrying wires serve for mechanical and electrical connection of self-supporting wires.
Admitted mechanical stress on the crimped connection for carrying wires makes up 40% of its tensile strength when connected to a SSIC wire and 20% in case of copper wire crimping.Reduced Al nominal cross section: -
Material: EV000072
Voltage row: IEK_V0000222
SIP section, RH part: 6.0
SIP section, LH part: 16.0
Color of RH sealed ring: EV000083
Color of left sealed ring: EV000080
Length: 73.0
Outer diameter: 18.5
Internal diameter 1: 3.3
Internal diameter 2: 5.3
Weight: 0.02
Operating temperature range: -50...+60
Application: IEK_V0000226
Matrix Type for Sleeve Slip: IEK_V0000223
Pret: 10,02 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/gia-06-16-bushings-pentru-self-supporting-insulated-conductor-s-with-a-carrying-neutral-mjpb-06-16-310341