

IEK GIA 16-25 INSULATED BUSHINGS (MJPB 16-25)

GIA bushings for self-carrying wires serve for mechanical and electrical connection of self-supporting wires. Admitted mechanical stress on the crimped connection for carrying wires makes up 40% of its tensile strength when connected to a SSIC wire and 20% in case of copper wire crimping.GIA bushings for self-carrying wires serve for mechanical and electrical connection of self-supporting wires.
Admitted mechanical stress on the crimped connection for carrying wires makes up 40% of its tensile strength when connected to a SSIC wire and 20% in case of copper wire crimping.Reduced Al nominal cross section: -
Material: EV000072
Voltage row: IEK_V0000222
SIP section, RH part: 16.0
SIP section, LH part: 25.0
Color of RH sealed ring: EV000080
Color of left sealed ring: EV000236
Length: 73.0
Outer diameter: 18.5
Internal diameter 1: 5.3
Internal diameter 2: 6.5
Weight: 0.02
Operating temperature range: -50...+60
Application: IEK_V0000226
Matrix Type for Sleeve Slip: IEK_V0000223
Pret: 11,92 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/gia-16-25-insulated-bushings-mjpb-16-25-310345