





IEK BUSHINGS PENTRU SELF-SUPPORTING INSULATED CONDUCTOR S WITH A CARRYING NEUTRAL GIF50-35 (MJPT 50-35)

GIN bushings for wires with a carrying neutral serve for mechanical and electrical connection of neutral conductors within SSIC networks with a carrying neutral. Admitted mechanical stress on the crimped connection for carrying wires makes up 95% of its tensile strength.GIF bushings for wires with a carrying neutral serve for mechanical and electrical connection of phase wires within SSIC networks with a carrying neutral.

Admitted mechanical stress on the crimped connection for carrying wires makes up 60% of its tensile strength.Reduced Al nominal cross section: -

Material: EV000072

Voltage row: IEK_V0000222 SIP section, RH part: 35.0 SIP section, LH part: 50.0

Color of RH sealed ring: EV000234 Color of left sealed ring: EV000233

Length: 98.0

Outer diameter: 22.0 Internal diameter 1: 9.0 Internal diameter 2: 8.0

Weight: 0.05

Operating temperature range: -50...+60

Application: IEK_V0000227

Matrix Type for Sleeve Slip: IEK V0000224

Pret: 16,36 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/bushings-pentru-self-supporting-insulated-conductor-s-with-a-carrying-neutral-gif50-35-mjpt-50-35-310357