

IEK BUSHINGS PENTRU SELF-SUPPORTING INSULATED CONDUCTOR S WITH A CARRYING NEUTRAL GIF70-35 (MJPT 70-35)

GIN bushings for wires with a carrying neutral serve for mechanical and electrical connection of neutral conductors within SSIC networks with a carrying neutral. Admitted mechanical stress on the crimped connection for carrying wires makes up 95% of its tensile strength.GIF bushings for wires with a carrying neutral serve for mechanical and electrical connection of phase wires within SSIC networks with a carrying neutral.
Admitted mechanical stress on the crimped connection for carrying wires makes up 60% of its tensile strength.Reduced Al nominal cross section: -
Material: EV000072
Voltage row: IEK_V0000222
SIP section, RH part: 35.0
SIP section, LH part: 70.0
Color of RH sealed ring: EV000202
Color of left sealed ring: EV000233
Length: 98.0
Outer diameter: 22.0
Internal diameter 1: 10.5
Internal diameter 2: 8.0
Weight: 0.05
Operating temperature range: -50...+60
Application: IEK_V0000227
Matrix Type for Sleeve Slip: IEK_V0000224
Pret: 16,50 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/bushings-pentru-self-supporting-insulated-conductor-s-with-a-carrying-neutral-gif70-35-mjpt-70-35-310359