



## **IEK BUSHINGS PENTRU SELF-SUPPORTING INSULATED CONDUCTORS WITH A CARRYING NEUTRAL GIF95-70 (MJPT 95-70)**

GIN bushings for wires with a carrying neutral serve for mechanical and electrical connection of neutral conductors within SSIC networks with a carrying neutral. Admitted mechanical stress on the crimped connection for carrying wires makes up 95% of its tensile strength. GIF bushings for wires with a carrying neutral serve for mechanical and electrical connection of phase wires within SSIC networks with a carrying neutral.

Admitted mechanical stress on the crimped connection for carrying wires makes up 60% of its tensile strength. Reduced Al nominal cross section: -

Material: EV000072

Voltage row: IEK\_V0000222

SIP section, RH part: 70.0

SIP section, LH part: 95.0

Color of RH sealed ring: EV000270

Color of left sealed ring: EV000202

Length: 98.0

Outer diameter: 22.0

Internal diameter 1: 12.2

Internal diameter 2: 10.5

Weight: 0.05

Operating temperature range: -50...+60

Application: IEK\_V0000227

Matrix Type for Sleeve Slip: IEK\_V0000224

Pret: 16,36 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/bushings-pentru-self-supporting-insulated-conductor-s-with-a-carrying-neutral-gif95-70-mjpt-95-70-310364>