

IEK BUSHINGS PENTRU SELF-SUPPORTING INSULATED CONDUCTOR S WITH A CARRYING NEUTRAL GIN 50 (MJPT 50N)

GIN bushings for wires with a carrying neutral serve for mechanical and electrical connection of phase wires within SSIC networks with a carrying neutral. Admitted mechanical stress on the crimped connection for carrying wires makes up 60% of its tensile strength.GIN bushings for wires with a carrying neutral serve for mechanical and electrical connection of neutral conductors within SSIC networks with a carrying neutral. Admitted mechanical stress on the crimped connection for carrying wires makes up 95% of its tensile strength.Reduced Al nominal cross section: -
Material: EV000072
Voltage row: IEK_V0000222
SIP section, RH part: 50.0
SIP section, LH part: 50.0
Color of RH sealed ring: EV000234
Color of left sealed ring: EV000234
Length: 175.0
Outer diameter: 25.0
Internal diameter 1: 9.0
Internal diameter 2: 9.0
Weight: 0.08
Operating temperature range: -50...+60
Application: IEK_V0000228
Matrix Type for Sleeve Slip: IEK_V0000224
Pret: 27,21 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/bushings-pentru-self-supporting-insulated-conductor-s-with-a-carrying-neutral-gin-50-mjpt-50n-310367