

IEK GIN 54 BUSHINGS PENTRU SELF-SUPPORTING INSULATED CONDUCTOR S WITH A CARRYING NEUTRAL (MJPT 54N)

GIN bushings for wires with a carrying neutral serve for mechanical and electrical connection of phase wires within SSIC networks with a carrying neutral. Admitted mechanical stress on the crimped connection for carrying wires makes up 60% of its tensile strength.GIN bushings for wires with a carrying neutral serve for mechanical and electrical connection of neutral conductors within SSIC networks with a carrying neutral. Admitted mechanical stress on the crimped connection for carrying wires makes up 95% of its tensile strength.Reduced Al nominal cross section: -
Material: EV000072
Voltage row: IEK_V0000222
SIP section, RH part: 54.6
SIP section, LH part: 54.6
Color of RH sealed ring: EV000206
Color of left sealed ring: EV000206
Length: 175.0
Outer diameter: 25.0
Internal diameter 1: 10.0
Internal diameter 2: 10.0
Weight: 0.08
Operating temperature range: -50...+60
Application: IEK_V0000228
Matrix Type for Sleeve Slip: IEK_V0000224
Pret: 23,32 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/gin-54-bushings-pentru-self-supporting-insulated-conductor-s-with-a-carrying-neutral-mjpt-54n-310368