



### **IEK NIM-TYPE SEALED INSULATED CAPS NIM150 (CPTAU 150 D25)**

NIM caps are applied for aluminum and copper stranded wires. Intended for a sealed multicore cables termination by means of crimping. Each wire size is shown with the help of a colored sealing ring. Inner chamber of aluminum part is filled with couplant protecting the aluminum surface from corrosion, lowering the contact resistance that contributes to reducing electric losses as well as ensuring a stable electric contact the within copper-aluminum system that protects the connection point from contact electrochemical corrosion. Polymer insulating material is resistant to UV and weather conditions. The bushing construction provides for ensuring tightness of 6 kW (50 Hz frequency) for 1 min at a depth of 1 meter. To attain these ratings, it is necessary to strip the correspondent insulation layer from the wire. The required stripping length is indicated on the bushing. Stripping border should be flat. Insulation thickness should be maintained at on the same level up to the stripping line. The wire should be inserted into the device until bumping. Wire crimping should be done from the center edgeward complying with the crimping border and number of crimpings indicated on the device. Admitted mechanical stress on the crimped connection for carrying wires makes up: – 1200 N for cables of 16 and 25 mm<sup>2</sup> in section; – 2500 N for cross-sections of 35, 50, 54, 70 and 95 mm<sup>2</sup>. NIM caps are applied for aluminum and copper stranded wires. They are intended for a sealed multicore cables termination by means of crimping. Each wire size is shown with the help of a colored sealing ring. Inner chamber of aluminum part is filled with couplant protecting the aluminum surface from corrosion, lowering the contact resistance that contributes to reducing electric losses as well as ensuring a stable electric contact the within copper-aluminum system that protects the connection point from contact electrochemical corrosion. Weight: 0,125

Diameter mounting hole: 13.0

Diameter of conductor hole: 15.5

Material: EV003894

Nominal voltage: ? 1000

Total length: 118.0

Al-rated cross section: 150.0

St nominal cross section: 150

Ambient temperature: -50...+60

Matrix Type for Sleeve Slip: IEK\_V0000225

Cross section form: EV010032

Color of sealed ring: EV000524

Pret: 53,24 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/nim-type-sealed-insulated-caps-nim150-cptau-150-d25-310373>