www.MATERIALE ELECTRICE.ro
Consiliere specializata



IEK BRIDA ZSGP 35-120/25-95 (CDR/CN 1S 95 UK)

ZSGP series clamps are intended for connecting SSIC to trunk non-insulated lines. Appropriate for aluminum and copper conductors under 1kW. When the screw bolts are tightened, spade terminal blades form a secured electrical connection, piercing the splitter conduit’s insulation and simultaneously fastening the trunk non-insulated line surface. When a definite stress sufficient for creating a stable electrical connection is reached, the upper screw-bolt head is separated. For mounting and transportation convenience, each screw-bolt is laminated for preventing possible disconnection of component parts. Clamp casing is made of mechanically strong thermoplastic reinforced with fiberglass. In case if there is a necessity to dismantle the clamp, it can be done using a correspondent wrench. To attain correspondent sealing values, the branched line wire should be inserted into the cap until bumping.For mounting and transportation convenience, each screw-bolt is laminated for preventing possible disconnection of component parts.
Clamp casing is made of mechanically strong thermoplastic reinforced with fiberglass.
In case if there is a necessity to dismantle the clamp, it can be done using a correspondent wrench.
To attain correspondent sealing values, the branched line wire should be inserted into the cap until bumping.Nominal voltage: 1000
Nominal cross section transition: 35...120
Nominal cross section branch: 25...95
Type of connection: EV004362
Ambient temperature: -60...55
Nominal clamp current: 190
Moment of screw head failure during installation: 25
Rated insulation voltage Ui: 6000
Length: 60
Width: 100
Height: 101.0
Weight: 0,266
: 35...120
: 25...95

Pret: 48,17 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/brida-zsgp-35-120-25-95-cdr-cn-1s-95-uk-310432