

IEK TERMOCONTRACTIBIL TTUK4,8/2,4 2:1 TRANSPARENT WITH GLUE 1 M

Designed for sealing and insulation of all types of connections of power cables with paper oil-impregnated insulation, plastic insulation, cross-linked polyethylene insulation. Inner surfaces of base and branches of multiple cable joint are coated with adhesive thermomelting layer that ensures perfect sealing after shrinkage.Being evenly applied on the entire inner surface of the tube, the adhesive layer provides complete sealing of the connection after shrinkage of the tube.Model: EV009930
Inner diameter before heat-shrink: 4,8
Inner diameter after heat-shrink: 2,4
Colour: EV000184
Material: EV003904
Shrink rate: EV009534
Wall thickness after shrinking: 0,8
Length: 1
Operation temperature: -55...125
Mounting temperature: -10...50
AC 50 Hz operating voltage: ? 660
Tensile strength: ? 10,4
Volumetric electrical resistance: ? 1x10^14
For dielectric strength up to: ? 15
Min shrinkage start temperature: 70
Min full shrinkage temperature: 125
Thickness of adhesive layer after full thermus: 0,4
Type: EV004267
Pret: 3,64 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/termocontractibil-ttuk4-8-2-4-2-1-transparent-with-glue-1-m-310451