

IEK TERMOCONTRACTIBIL STTK 115/35 3:1 NEGRU WITH GLUE 1 M/PACK.

Designed for sealing and insulation of all types of connections of power cables with paper oil-impregnated insulation, plastic insulation, cross-linked polyethylene insulation. Inner surfaces of base and branches of multiple cable joint are coated with adhesive thermomelting layer that ensures perfect sealing after shrinkage.Being evenly applied on the entire inner surface of the tube, the adhesive layer provides complete sealing of the connection after shrinkage of the tube.
Black marking on the tubes with the indication of the diameter before and after shrinking.Model: EV009930
Inner diameter before heat-shrink: 115
Inner diameter after heat-shrink: 35
Colour: EV000206
Material: EV003904
Shrink rate: EV009535
Wall thickness after shrinking: 3,1
Length: 1
Operation temperature: -40...110
Mounting temperature: -10...50
AC 50 Hz operating voltage: ? 1000
Tensile strength: ? 13
Volumetric electrical resistance: ? 1x10^12
For dielectric strength up to: ? 10
Min shrinkage start temperature: 120
Min full shrinkage temperature: 150
Thickness of adhesive layer after full thermus: 1,0
Type: EV004267
Pret: 108,17 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/termocontractibil-sttk-115-35-3-1-negru-with-glue-1-m-pack-310473