



IEK TERMOCONTRACTIBIL TTK 12/3 4:1 NEGRU WITH GLUE 1 M

Designed for sealing and insulation of all types of connections of power cables with paper oil-impregnated insulation, plastic insulation, cross-linked polyethylene insulation. Inner surfaces of base and branches of multiple cable joint are coated with adhesive thermomelting layer that ensures perfect sealing after shrinkage. Being evenly applied on the entire inner surface of the tube, the adhesive layer provides complete sealing of the connection after shrinkage of the tube.

Black marking on the tubes with the indication of the diameter before and after shrinking. Model: EV009699

Inner diameter before heat-shrink: 12

Inner diameter after heat-shrink: 3

Colour: EV000206

Material: EV000154

Shrink rate: EV009536

Wall thickness after shrinking: 0,5

Length: 1

Operation temperature: -40...110

Mounting temperature: -10...50

AC 50 Hz operating voltage: 1000

Tensile strength: ? 13

Volumetric electrical resistance: ? $1 \cdot 10^{12}$

For dielectric strength up to: ? 10

Min shrinkage start temperature: 120

Min full shrinkage temperature: 150

Thickness of adhesive layer after full thermus: 1,8

Type: EV004267

Pret: 10,42 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/termocontractibil-ttk-12-3-4-1-negru-with-glue-1-m-310477>