www.MATERIALE ELECTRICE.ro
Consiliere specializata



IEK TERMOCONTRACTIBIL KV(N)TP 4X16/25CU IZOLATIE DIN HARTIE 1KW

KV(N)tp-1 heat-shrink sleeve is designed for termination of aluminum or copper conductors of cables with impregnated-paper insulation for voltages up to 1 kV: AAG-1, AASh-1, AAB-1, AAP-1, AABSh-1, AAPSh-1, ASG-1, AASSh-1, ASBSh-1, SG-1, SSh-1, SBSh-1, SB-1, SP-1, SK-1, SBG-1, SPG -1, their equivalents and versions.Perfectly leak-tight sleeve design due to:
– use of high-quality two-layer heat-shrink materials with adhesive thermomelting coating on inner surfaces of tubes
and multiple cable joints;
– oil-resistant tubes put over phase insulation of cable conductors;
– use of special sealant for hydrochemical protection, applied over cable sheath and armor grounding assembly.
The sleeve is of universal type and can be used both outdoors and indoors in compartments with any level of humidity.
The cable sheath and armor grounding set is available for ordering with materials suitable for soldering or with constant-force springs made from high-quality stainless steel AISI 301 with high content of chromium and nickel.Suitable for: EV009707
Model: EV004267
Voltage row: EV004258
Nominal cross section: 16...25
Type of insulation material: IEK_V0000183
Installation Type: IEK_V0000187
Complete set: IEK_V0000188
Number of cores wiring: 4
Tip Type: IEK_V0000189
Attachment of the grounding bus to the cable: IEK_V0000192
Nominal voltage: 1
Material: IEK_V0000193
Min full shrinkage temperature: 120

Operating temperature range: -45...+50
Shrink rate: EV009535
Grounding bus Material: EV004186
External grounding bus attachment: IEK_V0000194
Number of conductors: 4
Pret: 381,52 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/termocontractibil-kv-n-tp-4x16-25cu-izolatie-din-hartie-1kw-310514