



### **IEK TERMOCONTRACTIBIL STT(TP)4X150/240CU IZOLATIE DIN HARTIE 1KV**

Stt(tp)-1 heat-shrink sleeve is designed for connection of aluminum or copper conductors of cables with impregnated-paper insulation for voltage 1 kV: AAG-1, AASh-1, AAB-1, AAP-1, AABSh-1, AAPSh-1, ASG-1, AASSh-1, ASBSh-1, SG-1, SSh-1, SBSH-1, SB-1, SP-1, SK-1, SBG-1, SPG -1, their equivalents and versions. The sleeves can be installed directly in the ground, tunnels and channels and also outdoors: on trestles, cable shelves, etc.

Perfectly leak-tight sleeve design due to:

- use of high-quality two-layer heat-shrink materials with adhesive thermomelting coating on inner surfaces of tubes and multiple cable joints;
- oil-resistant tubes put over phase insulation of cable conductors;
- use of special sealant for hydrochemical protection, applied over cable sheath and armor grounding assembly. Voltage row: EV004258

Model: EV004267

Number of conductors: 4

Nominal cross section conductor: 150...240

Suitable for: EV000154

Type of insulation material: IEK\_V0000183

Installation Type: IEK\_V0000187

Complete set: IEK\_V0000188

Connector Type: IEK\_V0000189

Attachment of the grounding bus to the cable: IEK\_V0000192

Nominal voltage: 1

Material: IEK\_V0000193

Min full shrinkage temperature: 120

Operating temperature range: -45...+50

Shrink rate: EV009535

Pret: 624,97 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/termocontractibil-stt-tp-4x150-240cu-izolatie-din-hartie-1kv-310538>