www.MATERIALE ELECTRICE.ro
Consiliere specializata



IEK TERMOCONTRACTIBIL PSTTBE 4X16/25 WITH PVC ISOLATION 1KV

PSttbe-1 heat-shrink sleeve is designed for connection of aluminum or copper conductors of cables with plastic, rubber and polyethylene insulation with armor or shield for voltage 1 kV: AVBbShv-1, VBbShv-1, AVVB-1, AVVBG-1, VVB-1, VVBG-1, APvBbShv-1, PvBbShv-1, VVGE, AVVGE, PvVGE, APvVGE, their equivalents and versions. The sleeves can be installed under ground (directly in the ground, in tunnels and channels) and outdoors (on trestles, cable trays, etc).The sleeves can be installed directly in the ground, tunnels and channels and also outdoors: on trestles, cable shelves, etc.
The sleeve set includes a kit of soldered or not soldered grounding options. The soldered grounding kit contains constant force springs (CFS) made from high-quality stainless steel AISI 301 with high content of chromium and nickel, that ensure reliable and safe connection of PML grounding bus to cable armor bands. Perfectly leak-tight sleeve design due to: – use of high-quality two-layer heat-shrink materials with adhesive thermomelting coating on inner surfaces of external casing, tubes and multiple cable joints.Voltage row: EV004258
Model: EV004267
Number of conductors: 4
Nominal cross section conductor: 16...25
Suitable for: EV000154
Type of insulation material: IEK_V0000184
Installation Type: IEK_V0000187
Complete set: IEK_V0000195
Connector Type: IEK_V0000189
Attachment of the grounding bus to the cable: IEK_V0000192
Nominal voltage: 1
Material: IEK_V0000193
Min full shrinkage temperature: 120
Operating temperature range: -45...+50
Shrink rate: EV009535
Pret: 195,64 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/termocontractibil-psttbe-4x16-25-with-pvc-isolation-1kv-310602