





IEK CONTACTOR KMI46562 65A IN A PROTECTIVE ENCLOSURE UE=380V/AC3 IP54

KMI AC contactors with thermal electrical relay in a protective enclosure represent a complete device consisting of a compact contactor KMI, RTI thermal electrical relay, enclosure with glands and control buttons. Intended for remote actuation by means of direct connection to the network and shutting down three-phase asynchronous electric motors with a short-circuited rotor for the applied voltage limited to 400 V as well as for protecting electric motors from overloads of inadmissible duration and overcurrents arising in case of one phase retardation. Applying KMI 10910 + KMI 23211 contactors predetermines the use of a plastic enclosure; KMI 34012 + KMI 49512 are supplemented with a metal one. Correspond to the requirements of EN 60947-1, EN 60947-5-1.Low noise.

High electrical wear resistance.

Wide range.Rated control supply voltage Us at AC 50HZ: 400

Rated control supply voltage Us at DC: -Voltage type for actuating: EV000460 Rated operation power at AC-3, 400 V: 30

Rated operation current Ie: 80

Conditioned rated short-circuit current Iq: 3
Setting range over-current release: 48...65
Connection type main current circuit: EV000154

Connection type main eartest enealt. Lv

Degree of protection (IP): EV006419

Pret: 618,48 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/contactor-kmi46562-65a-in-a-protective-enclosure-ue-380v-ac3-ip54-311657