

IEK PORNIRE MOTOR KMI46562 65A IP54 WITH INDICATION UE=400V/AC3

KMI AC contactors with thermal electrical relay in a protective enclosure represent a complete device consisting of a compact contactor KMI, RTI thermal electrical relay, enclosure with glands and control buttons. Intended for remote actuation by means of direct connection to the network and shutting down three-phase asynchronous electric motors with a short-circuited rotor for the applied voltage limited to 400 V as well as for protecting electric motors from overloads of inadmissible duration and overcurrents arising in case of one phase retardation. Applying KMI 10910 + KMI 23211 contactors predetermines the use of a plastic enclosure; KMI 34012 + KMI 49512 are supplemented with a metal one. Correspond to the requirements of EN 60947-1, EN 60947-4-1, EN 60947-5-1.There is one NO contact group built in the control coil module in the circuit of every contactor. Owing to the push-button control station, this provides for assembling a simple control circuit.Rated control supply voltage Us at AC 50HZ: 230
Rated control supply voltage Us at DC: -
Voltage type for actuating: EV000460
Rated operation power at AC-3, 400 V: 30
Rated operation current Ie: 80
Conditioned rated short-circuit current Iq: 3
Setting range over-current release: 48...65
Connection type main current circuit: EV000415
Degree of protection (IP): EV006419

Pret: 721,68 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/contactor-kmi46562-65a-ip54-with-indication-ue-400v-ac3-311659