www.MATERIALE ELECTRICE.ro
Consiliere specializata



IEK CONTACT EXTENSIONS PKI-22 ADDITIONAL CONTACTS 2Z+2P

PKI contact devices are intended for expanding the possibilities of contactor application within technology project automation systems.High speed response.Type of set-up: EV003970
Contactor design: ??? ????????????? ???, ???
Voltage type for actuating: EV000509
Rated operation current Ie at AC-15, 230 V: 6.0
Rated operation current Ie at DC-13, 230 V: 1.5
Rated control supply voltage Us at AC 50HZ: 660/400/230
Rated control supply voltage Us at DC: 400/220
Number of contacts as normally closed contact: 2
Number of contacts as normally open contact: 2
Min on capability at min current: 10.0
Min on capability at min voltage: 24.0
Max short-term load: 100.0
Thermal resistance current: 10.0
Insulation resistance: 10.0
Rated insulation voltage Ui: 690
Max. conductor cross section: 2?2,5
Mechanical wear resistance: 1,6?10^6
Degree of protection (IP): EV006405
Operating temperature range: -40...+50
Ambient class: IEK_V0000010
Maintainability: EV000494
Nominal operating DC DC-13 400 V: 0.63
Nominal operating current Ie at AC-15 660 V: 1.50
Nominal operating current Ie at AC-15 400 V: 3.00
Width: 44.0
Height: 47.0

Depth: 38.0
Weight: 0.05
Pret: 21,14 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/contact-extensions-pki-22-additional-contacts-2z-2p-311845